

BS Softlube

Synthetic chain lubricant for carton packaging.

BS Softlube advantages:

- suitable for water of any hardness;
- do not foam at all, thus escaping an undesirable layer of foam on the belts and floors;
- do not contain phosphates;
- efficient, avoids an expensive conveyor belts cleaning process;
- Excellent lubrication - the product covers conveyor belts with a protective film, which ensures a safe and permanent lubrication. This feature allows to extend spray intervals from 4 to 5 times, comparing to ordinary conveyor belts lubricants;
- "dry" lubricant - prevents cartons from sopping;
- low consumption product, reduces sewage contamination;
- the solution is neutral, so it can be used on all surfaces;
- silicone lubricant for conveyor belts' transporting laminated cardboard packaging.

Instructions for use

BS Softlube suitable for any hardness water. The most efficient is to dose the product into conveyor belts' lubricating water. Strong lubricating power allows extending spray intervals significantly. Dilution depends on the type of packaging, conveyor belts' speed and construction.

Information for safe use

Use common rules while working with chemical materials. Do not mix with other chemical materials. Keep tightly closed in original packaging, away from direct sunlight and sudden changes of the temperature. In storage facilities the temperature must be 0°C - +35°C.

Methodology for determining the concentration

Submitted separately.

Physical and Chemical Properties

Physical state	Liquid
Color	Whitish
Odour	Typical
pH (100 %, 20°C)	7,5 – 8,6
Relative density, 20°C	1,00 g/cm ³

Note: The above-mentioned information is typical for normal production and should not be considered as specifications.